



MORRIS was founded in 1977 with headquarter in Taiwan. It has enjoyed a great reputation by providing full range of superior quality products of gas welding and cutting equipment to its worldwide customers.

All the design and manufacture of Morris' products strictly conform to ISO and international standard. Its quality management system and procedure of the production are also complying with ISO 9001 & ISO 13485. Besides, Morris also has obtained the certificates of UL, CE and GMP for its industrial and medical products.

Morris is not only your best partner but also makes your life safer and easier.

Enjoy it on the professional gas welding & cutting equipment and medical apparatus.

MORRIS PRECISION TECHNOLOGY CO., LTD.



No.7-1 Kung Yeh Rd., Kuan Tien Ind. Dist. Tainan City, Taiwan 72042









INDUSTRIAL PROFESSIONAL GAS WELDING & CUTTING EQUIPMENT

Promise to give you... Professional Quality and Safest Devices. Taiwan making, IOXYGEN only.



OXY-ACETYLENE TORCH KITS (9)



These versatile torch kits are perfect for welding, cutting, gouging and heating. The regulators and cutters are made by brass materials for durability and longer life. Complete accessory package with hose, spark lighter, goggles, tip cleaners and replacement O-rings to convenience by operator. Each kit is presented in an easy-to-carry durable toolbox, clamshell or carry case for safe storage and easy transportation.



VMCW-22TB

Net Weight: 10.2kg

This medium-duty torch kit cuts up to 6" (150mm) with optional tips. It welds up to 3/8" (9mm) steel with optional tips.

Specification:

Torch	Cutting	Check	Oxygen	Acetylene	
Handle	Attachment	Valve	Regulator	Regulator	
VM-221	VM-222	88-3FGR 88-3FGL	VM-7M	VM-1.4M	

Tips(Size)			Accessories	
Welding	Heating	Cutting	Accessories	
VM-W (0,2,4)	VM-H (6)	3-101 (0)	Twin Hose:15Fts 1/4" w/fittings, Sparklighter, Googles and Tip Cleaners.	

VMCW-19P







VHCW-21TB



WELDING TORCH (9)





SAFETY DEVICE



H188/H288



Net Weight: 0.14kg / 0.16kg

- ▶ H188 for Torch / H288 for Regulator
- ► Max. pressure: Oxy 10bar / 15bar Ace 1.5 bar
- ▶ Nickel plated surface
- ▶ Function: None return valve Dust filter Flame arrest

FLOW METER (9) **REGULATOR**



Net weight: 1kg/each

- ▶ Outlet pressure at 3.5 Bar (Present)
- ▶ MIG/TIG applications for light to medium duty
- ▶ Machined Brass body with side entry.
- ▶ Single Stage and piston type construction
- ▶ Sintered metal inlet filter to trap impurities
- ▶ Absolute safety, durable, stable devices with accurate regulator for gas flow
- ▶ Economy style for easy maintenance
- ▶ Option kit available with 10 feet (3m) hose in clamshell packaging.

Specification:

Model No.	Gas	Flow (Lt./min)	Flow (ACFH)	Cylinder Pressure (Bar)	100 Feet Hose
100-25FL	Argon/	0-25		0-315	W/O
100-60CF	Co2		0-60	0-315	W/O

CUTTING TORCH





Net:1.26Kg(430mm)

Medium-duty cutting torch that has a cutting capacity up to 200mm steel with optional tips. Head mixing and built-in safety plug for maximum operator safety. The torch is standard 9/16"-18N inlet connections.

Specification:

<u>.</u>	Models		Length		Models		Length
YLENE	90° Head	70° Head	(mm)	NE	90° Head	70° Head	(mm)
1	42-4	42-4A	430	3OP	42-4F	42-4AF	430
Y L-A	42-4L	42-4AL	530	OXY-PROPANE	42-4FL	42-4AFL	530
)	42-4L(835)	42-4AL(835)	835	O	42-4FL(835)	42-4AFL(835)	835





SINGLE STAGE REGULATOR



VM Series



25 Series



